

## **75TS**

### **Production Information – August 2007**

#### **Description**

A glass cloth bases adhesive tape, designed for long term performance and resistance to continuous temperature exposure. Excellent mechanical and dielectric strength. Thermosetting rubber adhesive. (UL Approved)

#### **Applications**

- . **Motor phase insulation**
- . **Coil end fixing**
- . **Outer wrap of coil windings**
- . **Transformers and insulation**
- . **Cable Fixing**

#### **Technical Details**

<b>Total Thickness</b>	<b>0.18mm</b>
<b>Backing Thickness</b>	<b>0.12mm</b>
<b>Tensile Strength</b>	<b>280n/cm</b>
<b>Elongation</b>	<b>5%</b>
<b>Temperature</b>	<b>130°C Class B</b>
<b>Steel Adhesion</b>	<b>4.0 n/cm</b>
<b>Dielectric Strength</b>	<b>2500 Volts</b>
<b>Colours</b>	<b>Black, White</b>

#### **Note**

Unless otherwise indicated, the figures above are average values and should not be treated at face value for specification purposes. The Company reserves the right to improve products, and any change in specification will result in a re-issue of the information sheet. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modification or otherwise. Please check that you have the latest issue of the information sheet. All slitting and length tolerances are to British Standards, but other tolerances are available by request.