

<b>78TS</b>
-------------

**Production Information – August 2007**

**Description**

A strong acetate cloth coated with an acrylic adhesive system. Excellent mechanical and dielectrical strength.

**Applications**

- . Outer wrap of coil windings.
- . Repair of electrical equipment
- . cable Fixing
- . Motor phase insulation
- . Outer insulation for transformers

**Technical Details**

<b>Total Thickness</b>	<b>0.26mm</b>
<b>Backing Thickness</b>	<b>0.18mm</b>
<b>Tensile Strength</b>	<b>16kg / 25mm</b>
<b>Elongation</b>	<b>20%</b>
<b>Temperature</b>	<b>-30 to +130°C</b>
<b>Steel Adhesion</b>	<b>1000 grms / 25mm</b>
<b>Dielectric Strength</b>	<b>2500 Volts</b>
<b>Colours</b>	<b>Black, White</b>
<b>Insulation class</b>	<b>A (105°C)</b>

**Note**

Unless otherwise indicated, the figures above are average values and should not be treated at face value for specification purposes. The Company reserves the right to improve products, and any change in specification will result in a re-issue of the information sheet. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modification or otherwise. Please check that you have the latest issue of the information sheet. All slitting and length tolerances are to British Standards, but other tolerances are available by request.