

W9335

Production Information – September 2007

Description

High tack permanent adhesive with excellent ageing and weather resistant properties for automotive emblems, decals and mouldings, mirror fixings. Good resistance to solvents, chemicals, UV and heat.

Adhesive-	Acrylic (Solvent Based)
Tack-	J.Dow No. 20
Liner-	Green Polyolefin
Carrier-	High Performance PE Foam (96kg/m3)
Peel Adhesion-	PSTC-3 1.8 kg/25mm
Shear Strength-	PSTC-7 over 24 hours with 2 kg loading on 25mm x 25mm at 23°C sandwich holding of stainless steel plates.
Heat Resistance -	PSTC-9 over 24 hours with 0.5kg loading on 25mm x 25mm at 80°C sandwich holding of stainless steel plates.
Normal Tensile Strength-	Over 45kgs/25mm x 25mm
Colour	Black

Note

Unless otherwise indicated, the figures above are average values and should not be treated at face value for specification purposes. The Company reserves the right to improve products, and any change in specification will result in a re-issue of the information sheet. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modification or otherwise. Please check that you have the latest issue of the information sheet. All slitting and length tolerances are to British Standards, but other tolerances are available by request.